

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015384 A1

(51) International Patent Classification⁷: **G06F 9/06**

(21) International Application Number:
PCT/AU2004/001077

(22) International Filing Date: 12 August 2004 (12.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003904272 12 August 2003 (12.08.2003) AU

(71) Applicant and

(72) Inventor: ROBERTSON, Graeme, K. [AU/AU]; 525
Doyles Road, Shepparton East, VIC 3631 (AU).

(74) Agent: FREEHILLS CARTER SMITH BEADLE;
Level 43, 101 Collins Street, Melbourne, VIC 3000 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: SHOCK ABSORBER ASSEMBLY



(57) Abstract: A shock absorber assembly includes a motion damping means that is filled with a fluid in operation and has a pair of relatively moveable parts (12, 14) and valve means (26) permitting flow of the fluid between the parts. The parts comprise a first part (12) and a second part (14) in which the first part is receivable whereby the parts are arranged for relative retracting and extending movement during which fluid is forced through the valve means (26) at respective predetermined controlled flow rates so as to dampen the movement. The relatively moveable parts contain respective primary chambers (24, 29) for the fluid. The first part is substantially smaller in cross-section than the second part to define an intermediate chamber (52) about the first part within the second part. Lateral port means (56) communicates the intermediate chamber (52) and the primary chamber (24) of first part (12). The flows at respective predetermined controlled flow rates are limited to respective flows (i) directly from the primary chamber (24) of the first part (12) to the primary chamber (29) of the second part (14) and (ii) via the intermediate chamber (52) and lateral port means (56) from the primary chamber (29) of the second part (14) to the primary chamber (24) of the first part (12).

WO 2005/015384 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.